

# drought tips

Number 92-25

---

## Sprinkler Irrigation

---

Efficient sprinkler irrigation requires applying the right amount of water as evenly or uniformly as possible. Applying the right amount of water, in turn, requires knowing the soil moisture depletion, the application rate, and the depth applied.

### Estimating Application Rate and Depth Applied

The following equation can be used to estimate the sprinkler application rate:

$$i = (96.3 \times q) / (S_m \times S_l)$$

where:

$i$  = average application rate (inches per hour)

$q$  = average sprinkler discharge (gal/min)

$S_m$  = spacing along mainline (feet)

$S_l$  = spacing along lateral (feet)

The sprinkler discharge can be estimated by dividing the pump capacity by the number of sprinklers, or by inserting a hose over the sprinkler nozzle and measuring the time required to fill a 5-gallon container.

The average depth of applied water can be estimated by multiplying the application rate by the set time, or:

$$D = i \times T$$

where:

$D$  = average depth applied (inches);

$T$  = set time (hours)

### Estimating Irrigation Efficiency

Irrigation efficiency can be estimated by dividing the depth of beneficial use by the average depth applied, or:

$$E = BU \times 100 / D$$

where:

$E$  = irrigation efficiency (%)

$BU$  = beneficial use (inches)

The soil moisture depletion is the major component of  $BU$ . The soil moisture depletion can be estimated from CIMIS data, soil "feel" method, or neutron probe data. Another common component of  $BU$  is the leaching requirement, which is normally less than 5 percent for areas using surface water for irrigation.

Irrigation efficiencies should be 70 percent to 80 percent for hand-move and wheel-line systems, 80 percent to 90 percent for solid-set systems, and 80 percent to 90 percent for linear-move and center pivot systems. If the actual efficiency is less than these values, the set time should be reduced using the following equation:

$$T = (BU \times 100) / (E \times i)$$

where:

$E$  = desired irrigation efficiency

*Example:*

pump capacity = 300 gpm  
number of sprinklers = 60  
mainline spacing = 60 feet  
lateral spacing = 40 feet  
soil moisture depletion = 3 inches  
set time = 24 hours

1. Calculate the average application rate:

$$q = \text{pump capacity} / \text{number of sprinklers} = 300 \text{ gal/min} / 60 = 5 \text{ gal/min}$$

$$i = (96.3 \times 5 \text{ gpm}) / (40 \text{ feet} \times 60 \text{ feet}) = 0.20 \text{ inches per hour}$$

2. Calculate the average depth applied:

$$D = 0.20 \text{ inches per hour} \times 24 \text{ hours} = 4.8 \text{ inches}$$

3. Calculate the irrigation efficiency:

$$E = 3 \text{ inches} \times 100 / 4.8 \text{ inches} = 63\%$$

4. Calculate the set time needed for good efficiency for a hand-move system (desired efficiency = 75%):

$$T = (3 \text{ inches} \times 100) / 75 \times 0.20 \text{ inches per hour} \\ = 20 \text{ hours}$$

### Improving Sprinkler System Performance

The performance of a sprinkler system can be improved by the following measures:

1. Know the application rate and average depth applied.

2. Avoid overirrigating. Overirrigation means applying water in excess of the soil moisture depletion in the parts of the field receiving the least amount of water. Reduce overirrigation by decreasing the set time.

3. Irrigate during low wind periods (wind speed of less than 10 mi/h). Sprinkler uniformity is greatly reduced at wind speeds greater than 10 or 15 mi/h.

4. Offset lateral locations to improve seasonal uniformity. In offsetting, the lateral locations of the current irrigation are midway between the lateral locations of the previous irrigation.

5. Use the same nozzle size throughout the irrigation system. Mixing nozzle sizes results in nonuniform application rates.

6. Use flow-control nozzles for excessive pressure variations. Pressure variations of more than 20 percent between the pressure of the first nozzle

(closest to the pump) and last nozzle will cause nonuniform application rates. Flow-control nozzles reduce the variability in application rate caused by pressure variability. Flow-control nozzles are sized according to their discharge rates (gal/min).

7. Repair leaks in the irrigation system and replace or repair malfunctioning nozzles.

8. Prevent crop interference by using properly sized risers.

9. Maintain adequate pressure by adjusting the pump impeller (semi-open impellers), repairing or replacing a worn pump, or reducing the number of laterals operating.

---

***drought tips*** is a publication series developed as a cooperative effort by the following organizations:

California Department of Water Resources – Water Conservation Office  
University of California (UC)  
UC Department of Land, Air and Water Resources  
USDA Drought Response Office  
USDA Soil Conservation Service  
USDI Bureau of Reclamation, Mid-Pacific Region

The University of California, in compliance with Titles VI and VII of the Civil Rights Act of 1964, Title IX of the Education Amendments of 1972, Sections 503 and 504 of the Rehabilitation Act of 1973, and the Age Discrimination Act of 1975, does not discriminate on the basis of race, religion, color, national origin, sex, mental or physical handicap, or age in any of its programs or activities, or with respect to any of its employment policies, practices, or procedures. Nor does the University of California discriminate on the basis of ancestry, sexual orientation, marital status, citizenship, medical condition (as defined in Section 12926 of the California Government Code) or because individuals are special disabled veterans or Vietnam era veterans (as defined by the Vietnam Era Veterans Readjustment Act of 1974 and Section 12940 of the California Government Code). Inquiries regarding this policy may be addressed to the Affirmative Action Director, University of California, Agriculture and Natural Resources, 300 Lakeside Drive, 6th Floor, Oakland, CA 94612-3560, telephone: (510) 987-0097.

Published 1993